

# Excavators / E55w Compact Excavator

## Specifications & Options

■ Standard
  Optional
N/A Not Applicable

### Bobcat E55w

⊖ Engine	Standard	Long Arm
<b>Emissions Tier (EPA)</b>	Tier 3	Tier 3
<b>Engine Fuel</b>	Diesel	
<b>Maximum Governed RPM</b>	2,400 rpm	2,400 rpm
<b>Horsepower</b>	40.8 kW	40.8 kW
<b>Turbocharged Engine</b>	N/A	N/A

⊖ Performance	Standard	Long Arm
<b>Operating Weight</b>	5550 kg	5570 kg
<b>Weight Class</b>	5.5 t	5.5 t
<b>Travel Speed - High</b>	30 km/h	30 km/h
<b>Travel Speed - Low</b>	10 km/h	10 km/h
<b>Arm Digging Force</b>	27,000 N	24,000 N
<b>Bucket Digging Force</b>	41,000 N	41,000 N
<b>Boom Swing - Left</b>	80°	
<b>Boom Swing - Right</b>	50°	
<b>Maximum Dig Depth</b>	3.5 m	3.8 m
<b>Max Dump Height</b>	4.3 m	4.5 m
<b>Maximum Reach at Ground Level</b>	6.1 m	6.1 m

⊖ Capacities	Standard	Long Arm
<b>Fuel Tank</b>	120 L	

⊖ Hydraulic System	Standard	Long Arm
<b>Auxiliary Std Flow</b>	52.5 l/min	
<b>Auxiliary Pressure</b>	226 bar	

⊖ Dimansion	Standard	Long Arm
<b>Length</b>	6120 mm	6120 mm
<b>Overall Length in Travel Position</b>	6120 mm	6120 mm
<b>Width</b>	1920 / 2290 mm	1920 / 2290 mm
<b>Height</b>	2855 mm	2855 mm

⊖ Features	Standard	Long Arm
<b>Cab Enclosure</b>	■	■
<b>Cab Heater</b>	N/A	<input checked="" type="checkbox"/>
<b>Cab Air Conditioning</b>	■	■
<b>Radio</b>	■	■
<b>Tail Swing Type</b>	Conventional	Conventional
<b>Engine Shutdown</b>	N/A	N/A
<b>Auxiliary Hydraulics</b>	■	■
<b>Secondary Auxiliary Hydraulics</b>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<b>Quick Tach System</b>	N/A	N/A
<b>Rubber Track</b>	N/A	N/A
<b>Selectable Auxiliary Hydraulic Flow</b>	N/A	N/A
<b>Angle Blade</b>	N/A	N/A

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.